



Intrusion Detectors

Security

- Pet Immune Detector up to 60lb (27 kg) WS4904P
- Shock Sensor EV-DW4927
- Tri-Zone Door/Window Contact WS4965
- Vanishing Door/Window Contact EV-DW4975
- Door/Window Contact WS4945
- Recessed Door Transmitter EV-DW4917

Safety Sensors

Safety

- Wireless Photoelectric Smoke Detector WS4936
- Carbon Monoxide Detector WS4913
- Flood Detector WS4985

Keypads, Arming Devices & Panic Buttons

Remote Control

- 2-Way Wireless TouchScreen Arming Station WTK5504
- Wire-Free Keypad WT5500
- 5 Button Key WT4989
- 4 Button Key WS4939
- 2 Button Key WS4949
- 5 Button 12 Channel Key WS4959
- 1-Button Personal Panic WS4938

Sirens & Repeaters

Siren & Repeaters

- 2-Way Wireless Outdoor Siren WT4901
- 2-Way Wireless Indoor Siren WT4911
- Wireless Repeater WS4920

Control Panels

- DSC Touch - 7 inch 'All-in-One' TouchScreen SCW9067
- IMPASSA 2-Way Wireless Security System SCW9055/9057



SCW9067 Touch - 7 inch 'All-in-One' TouchScreen

- 7 inch TouchScreen with a resolution of 800x480
- Built in apps such as Contact info and Photo Frame
- Built in Camera, takes photos on Disarm and Alarm events
- Compatible with DSC 433 Mhz One-Way Wireless products
- Dual-Path Connectivity with Integrated Wi-Fi and Cellular
- Z-Wave, Bluetooth, Image Sensor and Cellular radios built in to work with smart home products
- Integrated with Alarm.com to offer Interactive Services through iOS and Android apps
- Software updates over Wi-Fi and manually with an SD card
- Supports 59 Wireless zones and 242 User codes
- Built in Two-way Voice over Cellular
- Built in Siren

Available in NA and AUS



SCW9055 / SCW9057 IMPASSA Self-Contained Wireless Security System

- Supports 64 wireless zones and 16 wireless keys (without using a zone slot)
- Optional integrated HSPA (3G) cellular, internet or dual communicator
- Cellular signal strength read-out to optimize placement
- Built-in 2-way audio VOX and push-to-talk alarm communication via phone line and cellular *
- 2-way audio is available only on IMPASSA 9057 Self-Contained Wireless Security System
 - 4 keypad support
 - 4 siren support
 - 16 wireless keys
- Easy wireless device enrollment process
- Template programming
- Full 32-character programmable labels
- 5 programmable function keys
- Individual FAP Emergency keys
- 17 user access codes
- 500 event buffer
- False alarm reduction features (CP-01)
- Enlarged keypad buttons
- Outdoor temperature display (requires wireless siren)
- Label library
- Compatible with leading edge interactive services (supported by DSC SCW9057 model only)

Available in NA, LATAM, EMEA and APAC

*2-way is available only on SCW9057

WTK5504 2-Way Wireless TouchScreen Arming Station

- 4.3" full color display
- AC plug-in
- Rechargeable batteries
- 24 hr battery back-up user programming user function
- Night light sleep mode
- Proximity arm/disarm (WTK5504P only)
- Voice chime/voice prompts
- Wall and desk stand mount
- Multi-language support
- 3-5 year battery life
- Tamper switch
- Compatible with IMPASSA, Alexor and PowerSeries (via TR5164-433)
- 5 programmable function keys
- 3 emergency keys
- Supports Alarm.com messaging

Available in NA, LATAM and APAC



WT5500 2-Way Wire Free Keypad

- 2x16 full message display
- Intuitive clock programming
- Multiple door chime
- Ambient light sensor
- Display and keymat backlighting
- Outdoor temperature display
- Wall and Deskstand* mount
- Proximity Tag PT4 Arm/Disarm (WT5500P Only)
- Installer's programming
- Multi-language support
- 5 programmable function keys
- 3 one-touch emergency keys
- Tamper switch
- Nominal battery life – 1 year
- Compatible with IMPASSA and PowerSeries (via TR5164-433)
- Visual armed status during sleep mode
- Blue LCD display screen
- Supports Alarm.com messaging
- Available in 433 MHz or 868 MHz

Available in NA, LATAM, EMEA and APAC

* WT5500D or WT5500DMK





3G2055 HSPA Cellular Alarm Communicator

- Compatible with IMPASSA Wireless Panel
- Back up and primary HSPA alarm communication
- Panel remote uploading/downloading support via cellular
- Supervision heartbeats via cellular
- 128-bit AES encryption via cellular
- SIA and Contact ID protocol
- Signal strength and trouble display via IMPASSA keypad
- Full event reporting
- Compatible with Sur-Gard System I-IP/II/III/IV/5 monitoring station receivers
- Command and Control via SMS (with IMPASSA v1.1 firmware)
- 2-Way voice over cellular (with IMPASSA v1.1 firmware)
- Antenna Extension Kits available: GS-8ANTP, GS-15ANTQ, GS-25ANTQ, GS-50ANTQ

Available in NA, LATAM and EMEA



3G8055(I) / CD8055(I) - IMPASSA HSPA / CDMA Cellular Alarm Communicator

- Compatible with IMPASSA v1.3+
- 4 integrated communicator models: 3G8055; 3G8055I*; CD8055**; CD8055I*/**
- 2 integrated cellular technologies: HSPA (3G); CDMA (only available in US)
- Cellular signal strength read-out to optimize placement
- Built-in Z-Wave automation
- Easy wireless device enrollment process
- Supports image sensors via virtual zones***
- Alarm.com AirFX Support
- Remote firmware upgradable over cellular
- Allows compatible web services
- Internal antennae

Available in NA, LATAM and APAC

* Required for supporting image sensors

** Only available in US

*** Only the (I) model



WS4945* / WS8945 Wireless Door/Window Contact

- Built-in reed switch
- Normally closed external contact input
- 1 lithium battery included
- Reliable 433 MHz or 868 MHz technology
- Available in white or brown housing
- Case and wall tamper

Available in NA, LATAM, EMEA and APAC

* WS4945N normally open version available



EV-DW4975 / EV-DW8975 Vanishing Contact

- Built-in reed switch
- Wafer-thin profile
- Long-life lithium battery included
- 5/8" (16 mm) magnet gap
- Reliable 433 MHz or 868 MHz technology
- Includes double-sided tape

Available in NA, LATAM and APAC



EV-DW4917 Wireless Recessed Door Transmitter

- Small, compact design
- Long-life lithium battery included
- Flexible mounting options (screw mount or press fit)
- Reliable 433 MHz technology
- Powerful, rare earth magnet
- Ships complete with flanged/non-flanged, brown/white access caps

Available in NA, LATAM and APAC



WS4965 Tri-Zone Wireless Door/Window Contact

- 3 zones in 1 (each zone has an individual serial number)
- 1 reed/magnet combination zone
- Tilt switch mode for overhead doors
- 2 normally closed external contact inputs
- Long-life lithium battery included
- 1/2" (13 mm) maximum magnet gap
- Low-battery LED indicator
- Case tamper
- Reliable 433 MHz technology
- Includes backplate

Available in NA, LATAM and APAC

WS4904 / WS8904 Wireless Passive Infrared Detector WS4904P Wireless Pet-Immune Passive Infrared Detector

- Based on the Bravo® 3D hardware motion detector
- High-traffic shutdown
- WS4904P features pet immunity up to 60 lb (27 kg)
- Fast and Slow detection settings for easy adjustment
- 1 lithium battery included
- Reliable 433MHz or 868 MHz technology
- 40ft detection range

Available in NA, LATAM, EMEA and APAC

* WS4904P offers enhanced wireless communication in areas with high RF noise



EV-DW4927SS Wireless Shock Sensor With Built-In Door/Window Contact

- Electro mechanical shock sensor
- Adjustable sensitivity
- Alarm pre-alert
- Built-in reed switch contact
- User-replaceable lithium battery
- 433MHz

Available in NA, LATAM and APAC



WT4989 / WT8989 2-Way Wireless Key

- Backlit ICON display
- Built-in buzzer for audible feedback
- Key tactile feedback
- 4 one touch function keys, programmable for up to 6 functions
- Status button indication
- Key-lock function to prevent accidental button presses
- Active alarm indication
- Water resistant
- Multifunction clip
- Nominal Battery life – 3 years
- Compatible with IMPASSA and PowerSeries (via TR5164-433)

Available in NA, LATAM, EMEA and APAC

WS4938 1-Button Personal Panic

- Activation via 1 large, easy-to-use button
- Integrated LED to indicate signal transmission
- Neck strap and multifunction belt clip included
- Reliable 433 MHz technology
- Water resistant
- Full 2-second delay on panic button
- Long-life lithium batteries included
- Optional wireless supervision

Available in NA, LATAM, EMEA and APAC



WS4949 2-Button Wireless Key

- 2-button, 3-function wireless key
- Activation via 2 large, scratch-resistant buttons
- Full 3-second delay on panic function
- Integrated LED to indicate signal transmission
- Reliable 433 MHz or 868MHz technology
- Long-life lithium batteries included
- Water resistant

Available in NA, LATAM and APAC



WS4939 / WS8939 4-Button Wireless Key

- Durable, scratch-resistant buttons
- 4 programmable function keys
- Long-life lithium batteries included
- Full 3-second delay on panic alarm to reduce false alarms
- Multifunction belt clip included
- Reliable 433 MHz or 868 MHz technology
- Optional generic rubber insert included
- Water resistant

Available in NA, LATAM, EMEA and APAC



WS4959 5-Button Wireless Key

- 12 programmable function keys
- Integrated tri-color LED to indicate signal transmission and security modes
- 4 durable, scratch-resistant buttons and center toggle button
- Multifunction belt clip included
- Reliable 433 MHz technology
- Full 3-second delay on panic function
- Long-life lithium batteries included
- Water resistant

Available in NA, LATAM and APAC



WS4913 / WS8913 Wireless CO Detector

- Slim-line design
 - Built-in 85dB alarm at 10 ft (3 m)
 - Malfunction supervision
 - Low sensitivity supervision
 - Electrochemical sensing technology
 - Transmits RF status, low battery and tamper condition
 - Hush feature
 - Wall tamper
 - 4-5 year battery life
- Onboard LEDs indicate:
 - Red – Alarm
 - Yellow – Trouble
 - Green – Power
 - Amber – Warm Up
 - End-of-Life (EOL) indicator (5 years)
 - Low battery supervision
 - Compatible with IMPASSA and PowerSeries v4.5 & higher
 - Reliable 433 MHz or 868 MHz technology



Available in NA, LATAM, EMEA and APAC

WS4936 Wireless Photoelectric Smoke Detector

- Automatic drift compensation
 - Built-in 85dB horn
 - Local test button
 - Low profile design
 - High/Low sensitivity reporting
- Easy-maintenance removable smoke chamber
 - Long-life lithium batteries included
 - UL/ULC listed for residential applications
 - Low battery indication



Available in NA

WS4985 / WS8985 Wireless Flood Detector

- Based on WS4945 wireless door/window contact
 - Water probe through a (1.8 m)6 foot-wire
 - Fully supervised
 - Built-in reed switch
- Normally closed external contact input
 - 1 lithium battery included
 - Case and wall tamper
 - End-of-line resistor
 - 4 year battery life



Available in NA, LATAM, EMEA and APAC



WT4901 / WT8901 2-Way Wireless Indoor Siren

- Siren Output – 85dB
 - Siren sounds for alarms, door chimes, entry/exit delay and troubles
 - Transmits RF status, low battery and tamper condition
- Front and back tamper detection
 - Nominal battery life – 1 year
 - Compatible with IMPASSA (433 MHz)
 - Onboard test button

Available in NA, LATAM, EMEA and APAC



WT4911 / WT8911 2-Way Wireless Outdoor Siren

- Siren Output – 100dB
 - Siren sounds for alarms and squawks
 - Strobe light functionality for visual indication
 - Provides temperature to WT5500 wire-free keypad
 - Transmits RF status, low battery and tamper condition
- Large print area for company logo
 - Front and back tamper detection IP34 rating
 - Nominal battery life – 2-3 years
 - Compatible with IMPASSA (433 MHz)
 - Remote test capability

Available in NA, LATAM, EMEA and APAC



WS4920 / WS8920 Wireless Repeater

- Greatly extends the range of DSC 1-way wireless devices
 - Backward compatible with existing security systems including, IMPASSA, PowerSeries and MAXSYS
 - WS4920 identifies the optimal location for mounting taking in to consideration noise and interference
 - Quick enrolment of DSC 1-way wireless devices
- Status LEDs for AC, battery and RF Jam
 - Up to four repeaters can be installed for each panel/receiver
 - WS4920 supports up to 164 wireless devices
 - Wall and case tamper protection
 - Aesthetically pleasing design

Available in NA, LATAM, EMEA and APAC